

**NPH series Non-Polarized+105°C wide temperature range standard 無極性+105°C 寬溫度品**

1. 適用於極性反轉回路，例如：信號交連或 HI-FI 高級音響設備如喇叭等。  
NP series capacitors are suitable for crossover network for HI-FI equipment's and speakers, etc.
2. 具容量誤差小，頻率回應高之特質。  
Have excellent frequency characteristic and small deviation of Capacitance.

**Specifications**

No	Item	Performance								
1	使用溫度範圍 Operating Temperature Range	-40 to +105°C								
2	定格電壓範圍 Rated Working Voltage Range	6.3-100V.DC								
3	靜電容量範圍 Capacitance Tolerance	0.1-1000μF								
4	靜電容量容許差 Capacitance Tolerance	±20%(at+20 °C,120Hz)								
5	洩漏電流 Leakage Current	After 5minutes application of rated voltage I≤0.03CV or 3 μ A minimum at 20°C								
6	損失角 Dissipation Factor(tan δ ) ( 120Hz+20°C )	Working Voltage (V)	6.3	10	16	25	35	50	63	100
		tan δ max.	0.25	0.25	0.20	0.20	0.15	0.15	0.12	0.10
7	溫度特性 (at 120 Hz) Characteristics at low temperature ( Impedance ratio at 120Hz )	Working Voltage (V)	6.3	10	16	25	35	50	63	100
		Z-25°C/+20°C	4	3	2	2	2	2	2	2
		Z-40°C/+20°C	8	6	4	4	4	4	4	3
8	高溫負荷特性 High Temperature Loading	After 1000hrs. application of DC rated working voltage at +105°C,with the polarity inverted every 250hrs,capacitors meet the characteristic of following requirements.								
		Leakage current	≤ the Initial specified value							
		Capacitance change	≤±25% of initial measured value							
		Dissipation Factor(tanδ )	≤200% of initial specified value							
9	高溫無負荷特性 Shelf Life	After 1000hrs. Application of DC no rated working voltage at +105°C,The capacitor shall meet the following limits: Post test requirements at + 20°C								
		Leakage current	≤200% of initial specified value							
		Capacitance change	≤±20% of initial measured value							
		Dissipation Factor(tanδ )	≤200% of initial specified value							


Multiplier for ripple current 紋波電流補正係數

Frequency Coefficient 周波數係數

μF	Frequency	60 (50) Hz	120 H z	400 H z	1K H z	≥10K H z
0.1~47		0.75	1.00	1.30	1.55	2.00
100~470		0.80	1.00	1.20	1.30	1.50
1000		0.85	1.00	1.10	1.10	1.15

Temperature Coefficient 周圍溫度係數

Coefficient	temperature (°C )	105	85	≤65
	coefficient	1.0	1.6	2.0

**NPH Series****Diagram of Dimensions**

DIMENSIONS &amp; MAXIMUM PERMISSIBLE RIPPLE CURRENT 規格尺寸及最大允許紋波電流

WV (SV) uF	6.3 (8)		10 (13)		16 (20)		25 (32)		35 (44)		50 (63)		63 (79)		100 (125)	
	SIZE	RC	SIZE	RC												
0.1															5×11	1
0.22															5×11	2
0.33															5×11	4
0.47											5×11	8			5×11	10
1											5×11	10			5×11	15
2.2											5×11	18	6.3×11	25	6.3×11	20
3.3											5×11	20	6.3×11	30	8×12	30
4.7							5×11	20	5×11	25	6.3×11	28	8×12	52	8×12	35
10					5×11	30	5×11	34	6.3×11	40	8×12	50	10×16	90	10×13	60
22			5×11	40	6.3×11	50	6.3×11	55	8×12	65	10×13	80	10×20	120	10×20	110
33	5×11	45	6.3×11	55	6.3×11	60	8×12	75	10×13	85	10×16	100	10×20	150	13×20	160
47	6.3×11	60	6.3×11	65	8×12	85	10×13	90	10×16	100	10×20	140	13×25	270	13×25	200
100	8×12	100	10×13	120	10×13	130	10×16	150	10×20	190	13×25	260	16×32	480	16×25	300
220	10×13	160	10×16	200	10×20	270	13×20	300	13×25	350	16×25	440				
330	10×16	220	10×20	270	13×20	340	13×25	400	16×25	480	16×32	580				
470	10×20	300	13×20	360	13×25	450	16×25	520	16×25	570						
1000	13×25	540	16×25	650	16×25	730	16×32	860								

Case size ØD×L (mm); Ripple current (mA rms) at 105°C, 120Hz